

DIN 1835B




$\lambda = 30^\circ$
 $\gamma = 10^\circ$

typ
HR



HSS
Co8



Použití / Usage / Applikation / Употребление

1 2 3 4 5 6 7 8 9 10 11 12 13

Krátké / Short / Kurz / Короткие

Dlouhé / Long / Lang / Длинные

D k 12	I	L	d h 6	Z	CODE
6	13	57	6	4	128518.060
7	16	66	10	4	128518.070
8	19	69	10	4	128518.080
9	19	69	10	4	128518.090
10	22	72	10	4	128518.100
11	22	79	12	4	128518.110
12	26	83	12	4	128518.120
13	26	83	12	4	128518.130
14	26	83	12	4	128518.140
15	26	83	12	4	128518.150
16	32	92	16	4	128518.160
17	32	92	16	4	128518.170
18	32	92	16	4	128518.180
20	38	104	20	4	128518.200
22	38	104	20	5	128518.220
24	45	121	25	5	128518.240
25	45	121	25	5	128518.250
26	45	121	25	5	128518.260
28	45	121	25	5	128518.280
30	45	121	25	5	128518.300
32	53	133	32	6	128518.320

D k 12	I	L	d h 6	Z	CODE
6	24	68	6	4	129518.060
8	38	88	10	4	129518.080
10	45	95	10	4	129518.100
12	53	110	12	4	129518.120
14	53	110	12	4	129518.140
16	63	123	16	4	129518.160
18	63	123	16	4	129518.180
20	75	141	20	4	129518.200
22	75	141	20	5	129518.220
24	90	166	25	5	129518.240
25	90	166	25	5	129518.250
26	90	166	25	5	129518.260
28	90	166	25	5	129518.280
30	90	166	25	5	129518.300
32	106	186	32	6	129518.320

1

2

3

4

5

6

7

8